

**Brand:** Ranger**Model:** R2600HD**Description:** Super-Duty Truck Tire Changer**Developed From All Aspects of Truck Wheel Service**

The Ranger R-2600HD is an incredibly fast and efficient large tire changer. Swap out tubeless truck, agricultural and off-road tires from 14" to 26" in just minutes. A portable remote control brings convenient precision to your finger tips and saves you precious time. We've thoroughly explored all aspects of truck wheel service to develop the quickest large tire changer possible. Experience your shortest floor-to-floor service times ever, making your job easier and more profitable. All of our changers are built with forged, hardened, and ground components designed to resist scoring, grooving, and wear. Our engineers understand that speed, convenience and safety are your top priorities, so we've made them ours! Ranger® tire changers are built to allow operators to learn and use them both quickly and safely, so you'll be up and running in no time flat.

**Features**

- Super-duty electric motor and hydraulic drive for superior torque and wheel holding power
- Self-centering hydraulic clamping chuck
- Heavy, tapered roller bearings and a dual direction hydraulic motor provide smooth torque
- Quick positioning and locking mount / demount arm
- Hydraulic sled carriage for positioning, bead loosening, mounting and demounting procedures
- Single piece frame for superior rigidity
- Hydraulically operated spreader jaws ensure secure clamping of virtually all rims and off-road style wheels
- Massive chuck spindle handles the heaviest loads
- Sturdy spindle, chuck and mount-demount head hydraulically rotates, raises, and lowers with simple operator controls
- Very gentle on over-the-road tires and tubeless tires mounted on aluminum wheels
- Easy to use

Specifications

- **Drive system:** electric / hydraulic
- **Standard voltage:** 208 V – 230 V / 60 Hz / 1 Ph
- **Wheel clamping method:** 4 clamps
- **Bead breaking system:** armor-plated disc
- **Max rim diameter:** 14" – 26" / 356 mm – 660 mm
- **Max tire / wheel diameter:** 63" / 1,600 mm
- **Max tire / wheel width:** 31" – 12" / 800 mm
- **Shipping weight:** 1,485 lbs. / 674 kg

