

**Brand:** Ranger**Model:** R26ST**Description:** Power-Assist Tilt-Back 26" Capacity Tire Changer**A Fast, No-Hassle Way to Service 26" Wheels**

A 26" wheel capacity tire changer with a single assist tower, the R26ST makes the once tedious chore of changing a tire a snap. Forget the clumsy adapters and awkward tabletop adjustments. The R26ST is a fast and no-hassle way to service up to 26" wheels. Designed to reduce technician fatigue, this changer instantly makes tire work safer and more efficient. Perfect for high-volume tire shops that service large, low profile tires.

Features

- 26" outside clamp
- Bead hold down device
- Oversize lube bucket storage
- Dual-setting bead breaker
- Single power-assistant / Tilt-back tower
- Air-lock mounting tool holder
- Inflation gauge with integrated air dump valve
- Inflation pressure regulator / limiter
- Inflation restraint device
- Water Filter / Oiler / Lubricator / Air Regulator
- Tool tray / bin storage / Includes Brush / Breaker Bar
- Lower-bead left and right lifting rollers
- Single bead lifting roller on the left
- Upper-bead assist roller
- Traveling drop-center hold down device
- Powerful high-torque motor
- Lower bead helper discs
- Powerful "jet-blast" bead sealer

Specifications

- **Drive system type:** electric / air
- **Motor:** 2 Hp / 110 - 220 VAC / 50 - 60 Hz / 1 Ph
- **Air requirement:** 110 - 175 psi / 8 - 12 bar
- **Wheel clamping method:** 4 internal / external clamps
- **Tool holder:** air-lock mounting
- **Table clamping system:** dual pneumatic cylinders
- **Bead breaking system:** pneumatic blade
- **Power assist towers:** single
- **Internal rim clamping capacity:** 14-1/2" - 28" / 368 mm - 711 mm
- **External rim clamping capacity:** 12-1/2" - 26" / 315 mm - 660 mm
- **Turntable tire width capacity mount:** 5" - 22" / 127 mm - 559 mm
- **Bead breaker tire width capacity demount:** 3" - 15" / 76 mm - 381 mm
- **Maximum tire diameter:** 47" / 1,194 mm
- **Shipping weight:** 1,025 lbs. / 465 kg
- **Shipping dimensions:** 45" x 57" x 72" / 1,143 mm x 1,448 mm x 1,829 mm

