

**Brand: Ranger****Model: RTJ-1****Description: 1-Ton Capacity Telescoping Transmission Jack****The Original and Still the Best**

TransJak's heavy lifting capabilities and top-notch construction make it the transmission service professional's first choice. Remove, transfer and install transmissions, transaxles and other drive-train components with ease. The fully-adjustable saddle adapts to just about any passenger car and light truck transmission or assembly. Plus, with its heavy-duty chain anchors and fail-safe overload system, you can feel secure—even with all that metal up in the air. It's just one of the reasons why The TransJak® is America's most popular trans jack.

Features

- Foot operated pump
- Two-stage design
- Fully adjustable saddle tilts four ways
- Heavy-steel construction for maximum durability
- Double-sealed hydraulics to prevent contamination for longer service life
- Heavy-duty chain anchors keep loads secure
- Steel roller bearings are included underneath the table and on the ends of the adjustment screw to minimize friction and allow for effortless table adjustment even when loaded
- Fully adjustable universal saddle adapts to passenger car and light truck automatic transmissions and transaxle assemblies.
- Fine-thread adjustment screws with oversized knobs make adjusting the table a cinch
- Two-stage design provides an extended lifting height of over 79"
- Hardened chrome-moly ram prohibits rust from entering hydraulic system
- Two individual push / pull handles for extra handling capability
- System overload system prevents the jack from being used beyond its rated capacity
- Extra-wide base and four heavy-duty swivel bell bearing casters provides a low center of gravity and exceptional maneuverability

Specifications

- **Lifting capacity – first stage:** 2,000 lbs. / 907 kg
- **Lifting capacity – second stage:** 1,000 lbs. / 454 kg
- **Lowered height:** 37" / 940 mm
- **Raised height:** 79-1/2" / 2,019 mm
- **Base dimensions:** 39" x 39" / 991 mm x 991 mm
- **Shipping weight:** 206 lbs. / 94 kg
- **Shipping dimensions:** 17" x 25" x 39" / 432 mm x 635 mm x 991 mm

