

**Brand:** Ranger**Model:** RX950AT**Description:** Power Assist 22" Capacity RimGuard Tire Changer**State-of-the-Art Features for Increased Service Capability**

The RX950AT 22" power assist RimGuard tire changer delivers true performance, unparalleled control, and increased efficiency. The RX950AT is a true "no compromises" package equipped with state-of-the-art features that increase service capability, customer satisfaction and profits. Rim-clamping and bead breaking operations are precise, ensuring that even today's expensive alloy wheels remain undamaged. The fully adjustable tool bar can be set for both vertical and horizontal planes, and the improved hardened alloy steel mount / demount head allows you to perform all changing functions in the same position. Top it off with a bead hold down device, lower bead helper disc, a 2 Hp motor, a "geometric" table design that allows you to inspect the underside of the wheel and a high volume "jet-blast" system for bead seating, and you've got yourself a total system tire and wheel service center to fulfill all your business needs.

Features

- 8-gallon surge tank
- Dual-setting bead breaker
- Bead hold down device
- Single assist tower
- Single power assistant
- Inflation gauge with integrated air dump valve
- Inflation regulator / limiter
- Oversize lube / soap bucket storage
- Inflation restraint device
- Bead lifting roller
- Tool tray / bin storage / Includes brush / Breaker bar
- Water filter / Oiler / lubricator / Air regulator
- Powerful high-torque motor
- Large storage trays
- Powerful "jet-blast" bead sealer
- Traveling drop-center hold down device
- For standard passenger and light truck service

Specifications

- **Wheel types:** aluminum, special alloys, steel
- **Drive system type:** electric / air
- **Motor:** 2 Hp / 110 - 220 VAC / 50 - 60 Hz / 1 Ph
- **Air requirement:** 110 - 175 psi / 8 - 12 bar
- **Wheel clamping method:** 4 internal / external clamps
- **Table clamping system:** dual pneumatic cylinders
- **Bead breaking system:** pneumatic blade
- **Internal rim clamping capacity:** 12-1/2" – 22" / 317 mm – 559 mm
- **External rim clamping capacity:** 11-1/2" – 21" / 292 mm – 533 mm
- **Turntable tire width mount capacity:** 3" – 14" / 76 mm – 355 mm
- **Bead breaker tire width demount capacity:** 3" – 14" / 76 mm – 317 mm
- **Maximum tire diameter:** 50" / 1,270 mm
- **Shipping weight:** 798 lbs. / 363 kg
- **Shipping dimensions:** 44" x 47" x 67" / 1,194 mm x 1,194 mm x 1702 mm

