




Brand: BendPak
Models: XP-12C
Description: Heavy-Duty Clearfloor Two-Post Lifts

- 12,000 pound lifting capacity.
- Dual hydraulic "direct-drive" cylinders.
- Electric/hydraulic power system.
- Large, oversize, 3/4" thick, A36 steel base plate.
- Single-point safety-lock release.
- Oversize 53" tall carriage for superior strength and durability.
- Self-lubricating, dura-glide polyethylene bearing system.
- Safety locks in each column spaced every 3-inches.
- Automatic arm restraints.
- Heavy-duty dual equalizer cables.
- Padded overhead safety-shutoff bar.
- Durable, rubber lift pads with stackable adapters.
- Truck and van adapters standard.



MODEL	XP-12C
Lifting Capacity*	12,000 Lbs. / 5443 Kg.
*Max Capacity / Front Axle	6,000 lbs. / 2722 Kg.
*Max Capacity / Rear Axle	6,000 lbs. / 2722 Kg.
A - Height Overall: (*)	170" / 4318 mm.
B - Width Overall (Outside of Base Plate):	155" / 3937 mm.
C - Width (Outside of Columns):	144" / 3658 mm.
D - Floor To Overhead Switch: (*)	165" / 4191 mm.
E - Inside Columns:	120" / 3048 mm.
F - Reach (Front Arm Min.):	39" / 991 mm.
G - Reach (Front Arm Max.):	59" / 1499 mm.
H - Reach (Rear Arm Min.):	39" / 991 mm.
I - Reach (Rear Arm Max.):	59" / 1499 mm.
J - Min. Pad Height:	5" / 127 mm.
K - Rise:	69" / 1753 mm.
L - Max Lift Height (Pad Only):	74" / 1880 mm.
M - Max Lift Height (6" Adapter):	80" / 2032 mm.
N - Drive-Thru Clearance:	106" / 2692 mm.
Motor (**)	220 VAC / 60 Hz. 1Ph.
Time of full Rise:	45 Seconds
Max Load Per Arm:	3,000 Lbs. / 1361 Kg.

* An optional bolt-on top extension for columns raises the overhead bar an additional 24". Must be ordered from factory at time of order.

** Special Voltages Available Upon Request.

The design, material and specifications are subject to change without notice.