



MODEL	HD-12SS-B	HD-12-B	HD-12X-B
Lifting Capacity*	12,000 lbs. / 5443 Kg.	12,000 lbs. / 5443 Kg.	12,000 lbs. / 5443 Kg.
*Max Capacity / Front Axle	6,000 lbs. / 2722 Kg.	6,000 lbs. / 2722 Kg.	6,000 lbs. / 2722 Kg.
*Max Capacity / Rear Axle	6,000 lbs. / 2722 Kg.	6,000 lbs. / 2722 Kg.	6,000 lbs. / 2722 Kg.
A - Overall Width	130" / 3302 mm.	130" / 3302 mm.	130" / 3302 mm.
B - Outside Length	181" / 4597 mm.	205" / 5207 mm.	253" / 6426 mm.
C - Overall Length	211" / 5360 mm.	235" / 5969mm.	283" / 7188mm.
D - Height of Columns	88" / 2235 mm.	88" / 2235 mm.	88" / 2235 mm.
E - Min. Runway Height	7" / 178 mm.	7" / 178 mm.	7" / 178 mm.
F - Max. Rise	70" / 1778 mm.	70" / 1778 mm.	70" / 1778 mm.
G - Max. Lifting Height	77" / 1956 mm.	77" / 1956 mm.	77" / 1956 mm.
H - Width Between Columns	116" / 2946 mm.	116" / 2946 mm.	116" / 2946 mm.
I - Runway Width	20" / 508 mm.	20" / 508 mm.	20" / 508 mm.
J - Width Between Runways (*)	32" - 49"	32" - 49"	32" - 49"
K - Length of Runways	813 mm. - 1245 mm.	813 mm. - 1245 mm.	813 mm. - 1245 mm.
Locking Positions	12	12	12
Lock Spacing	Every 4" / 102 mm.	Every 4" / 102 mm.	Every 4" / 102 mm.
Lifting Time	60 Seconds	60 Seconds	60 Seconds
Standard Motor (**)	220 VAC / 60 Hz. 1Ph.	220 VAC / 60 Hz. 1Ph.	220 VAC / 60 Hz. 1Ph.

* This dimension may be limited with the addition of rolling jacks. See rolling jack specifications on separate page.

** Special Voltages Available Upon Request

The design, material and specifications are subject to change without notice.