



Note: Power unit can be located at either "X" location.

MODEL	XPR-12C	XPR-15C
Lifting Capacity*	12,000 Lbs. / 5443 Kg.	15,000 Lbs. / 6804 Kg.
*Max Capacity / Front Axle	6,000 lbs. / 2722 Kg.	7,500 Lbs. / 3402 Kg.
*Max Capacity / Rear Axle	6,000 lbs. / 2722 Kg.	7,500 Lbs. / 3402 Kg.
A - Height Overall: (*)	170" / 4318 mm.	170" / 4318 mm.
B - Width Overall (Outside of Base Plate):	155" / 3937 mm.	155" / 3937 mm.
C - Width (Outside of Columns):	144" / 3658 mm.	144" / 3658 mm.
D - Floor To Overhead Switch: (*)	165" / 4191 mm.	165" / 4191 mm.
E - Inside Columns:	120" / 3048 mm.	120" / 3048 mm.
F - Reach (Front Arm Min.):	32" / 813 mm.	32" / 813 mm.
G - Reach (Front Arm Max.):	60" / 1524 mm.	60" / 1524 mm.
H - Reach (Rear Arm Min.):	32" / 813 mm.	32" / 813 mm.
I - Reach (Rear Arm Max.):	60" / 1524 mm.	60" / 1524 mm.
J - Min. Pad Height:	5" / 127 mm.	5" / 127 mm.
K - Rise:	69" / 1753 mm.	69" / 1753 mm.
L - Max Lift Height (Pad Only):	74" / 1880 mm.	74" / 1880 mm.
M - Max Lift Height (6" Adapter):	80" / 2032 mm.	80" / 2032 mm.
N - Drive-Thru Clearance:	106" / 2692 mm.	106" / 2692 mm.
Motor (**)	220 VAC / 60 Hz. 1Ph.	220 VAC / 60 Hz. 1Ph.
Time of full Rise:	45 Seconds	45 Seconds
Max Load Per Arm:	3,000 Lbs. / 1361 Kg.	3,750 Lbs. / 1701 Kg.
* An optional bolt-on top extension for columns raises the overhead bar an additional 24". Must be ordered from factory at time of order.		
** Special Voltages Available Upon Request.		
The design, material and specifications are subject to change without notice.		