

E0.8B8F1



Hydraulic Power Units

SKU# 5585315

1.6 Gal Reservoir, 1,900 PRV, 1.5 HP Motor, 110-230V / 50-60 Hz / 1 Ph, UL/ETL Listed

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

The "Little Brother" of Our Hydraulic Power Unit Collection

This [hydraulic power unit](#) is suitable for many lifting applications, but it was specifically designed for low-rise lifts. The 1.6-gallon oil reservoir is small but far from puny. In fact, low-rise scissor lifts are a popular choice for both commercial and home garages due to their versatility. The E0.8B8F1 power unit delivers reliably every time. Ranger power units can be mounted to multiple car lift models, but it's important to know what you're lifting before making a purchase.

Features

- High mechanical and volumetric efficiency
- End head prepared for lift-hold-lower applications using our manual lowering valve or solenoid cartridge valves.
- Totally enclosed motors are suitable for use in humid environments or dusty, contaminated atmospheres. UL Recognized AC electric motors feature heavy gauge steel frame and high-quality ball bearings.
- Torque load remains constant throughout operation.
- Heavy-duty start switches with a high IP-protection class and silver-plated contacts for a long service life.
- Cartridge-style relief valves meet tough demands for dependability and life expectancy.
- Minimum recommended temperature is -25°C (-13°F).
- Maximum recommended temperature is +80°C (+175°F).
- 12-months warranty



Specifications

| SKU# | Model | Reservoir | PRV | HP | Cert |
|---------|----------|-----------|-------|-----|--------|
| 5585280 | F2.1F3H1 | 3.6 gal | 2,850 | 2.5 | UL/ETL |
| 5585285 | E2.1F3H1 | 3.6 gal | 2,650 | 2.5 | UL/ETL |
| 5585315 | E0.8B8F1 | 1.6 gal | 1,900 | 1.5 | UL/ETL |
| 5585320 | E3.7K3H2 | 8.5 gal | 2,400 | 2.5 | UL/ETL |
| 5585325 | F3.2G3H1 | 4.2 gal | 2,650 | 2.5 | UL/ETL |
| 5585435 | E1.2B3F1 | 1.6 gal | 2,500 | 1.5 | CE |