

# F3.2G3H1



## Hydraulic Power Units

SKU# 5585325

4.2 Gal Reservoir, 2,650 PRV, 2.5 HP Motor, 208-230V / 50-60 Hz / 1 Ph, UL/ETL Listed

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

## Made to Last the Lifespan of Any Car Lift

A large, 4.2-gallon tank, 2.5 HP single-phase motor and 2,650 psi threshold on the pressure relief valve make for an incredibly versatile [hydraulic power unit](#) capable of servicing almost every car lift we make. This unit's 4.2-gallon tank is a little bigger than some in our collections, making it great for both extended-height lifts and heavier lifting applications. Every power unit made by Ranger Products is CE, UL and/or ETL-approved.

## Features

- High mechanical and volumetric efficiency
- End head prepared for lift-hold-lower applications using our manual lowering valve or solenoid cartridge valves.
- Totally enclosed motors are suitable for use in humid environments or dusty, contaminated atmospheres. UL Recognized and CSA Certified\* AC electric motors feature heavy gauge steel frame and high-quality ball bearings.
- Torque load remains constant throughout operation.
- Heavy-duty start switches with a high IP-protection class and silver-plated contacts for a long service life.
- Cartridge-style relief valves meet tough demands for dependability and life expectancy.
- Minimum recommended temperature is -25°C (-13°F).
- Maximum recommended temperature is +80°C (+175°F).
- 12-months warranty

## Specifications

SKU#	Model	Reservoir	PRV	HP	Cert
5585280	F2.1F3H1	3.6 gal	2,850	2.5	UL/ETL
5585285	E2.1F3H1	3.6 gal	2,650	2.5	UL/ETL
5585315	E0.8B8F1	1.6 gal	1,900	1.5	UL/ETL
5585320	E3.7K3H2	8.5 gal	2,400	2.5	UL/ETL
5585325	F3.2G3H1	4.2 gal	2,650	2.5	UL/ETL
5585435	E1.2B3F1	1.6 gal	2,500	1.5	CE

