

MDS-6EXT



Low-Mid Rise Lifts

SKU# 5175192

6,000-lb. Cap. / Mid-Rise Lift / Extended Platform / Open Center

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Extended-Length Mid-Rise Lift for Longer Wheelbases

Using long-wheelbase vehicles as our point of reference, we designed the MDS-6EXT [mid-rise lift](#) to accommodate longer lifting points that better reach the extreme edges of the vehicle underbody. Along with the flush-mount MDS-6EXTF, these two extended mid-rise lift models maintain their open-center design, just like our standard length MDS-6LP and MDS-6LPF models.



Features

- 6,000-lb. lifting capacity
- Open-center design
- Adjustable arm assemblies
- Solid-steel safety lock bars
- Multiple lock positions
- Hinge-point with Zerk grease fittings
- Low-profile design
- Rubber blocks included
- Removable ramps

Specifications

| | |
|---------------------------------|-----------------------------------|
| Lifting Capacity | 6,000 lbs. (2,724 kg) |
| Lift Height w/o Blocks | 36.6" (930 mm) |
| Lift Height + Blocks | 38.1" (968.5 mm) |
| Lift Platform Dimensions | 19" x 78.7" (484 mm x 2,000 mm) |
| Width Between Platforms | 40" to 46" (1,018 mm to 1,168 mm) |
| Overall Width | 19" (484 mm) |
| Overall Length | 104.3" (2,650 mm) |
| Lowered Height | 4.5" (116 mm) |
| Lifting Time | 35 sec |
| Motor (*) | 110-220 VAC / 60 Hz / 1 Ph |

* Special voltage available on request.

Design, materials, and specifications shown here are subject to change without notice.

Note: An air supply (minimum 50 psi / 10 CFM) is required for the safety-lock mechanisms to disengage. It is solely your responsibility to install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.