

# PL-6KDTX

## Parking Lifts

SKU# 5175212

12,000-lb. Cap. Parking Lift / Tandem / Independent Platforms  
Extra-Wide

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

## Extra-Wide Superstructure Tandem-Platform Parking Lift

For wide-clearance vehicles, we've made the columns of the PL-6KDTX [parking lift](#) a little wider. This ensures that truck mirrors gracefully pass through the lift structure, and vehicle doors have a little more room to open and close. Some folks find the extra space more accommodating when they need to access the vehicle.

This lift is intended for use by anyone with four vehicles and a wide garage area to store them. You'll be surprised to see how well this unit fits in a variety of garage sizes. In the right space, it can be successfully utilized for commercial or residential purposes.

## Features

- 6,000-lb. capacity per deck
- Perfect for cars, light trucks, motorcycles and ATVs
- Rugged I-beam and C-channel construction
- Built-in wheel stops
- Wide base-plate for maximum stability
- Front and rear wheel chocks
- Superstructure features durable powder-coat finish
- Dual hydraulic cylinders with heavy-duty steel lifting cable
- Heavy-duty steel construction
- Reliable electric-hydraulic power system
- Full-width platform to keep bottom vehicles protected
- Simple controls
- Oversized sheave diameter reduces cable fatigue
- High-speed lifting
- Features heavy-duty 3/8" aircraft cable
- Rugged 1.25" roller axles
- Multi-position safety locks in each column
- Runways feature non-skid surface
- Push-button pneumatic safety release
- Independent backup slack-cable safety latches
- Customizable power unit location



## Specifications

<b>Lifting Capacity</b>	6,000 lbs. (2,722 kg)
<b>Overall Width</b>	250" (6,350 mm)
<b>Overall Length</b>	236.5" (6,008 mm)
<b>Overall Height</b>	123.75" (3,140 mm)
<b>Min. Runway Height</b>	9" (230 mm)
<b>Max. Rise</b>	89" (2,261 mm)
<b>Width Between Posts</b>	225" (5,713 mm)
<b>Platform Width</b>	82" (2,086 mm)
<b>Platform Length</b>	152" (3,862 mm)
<b>Drive-thru Clearance</b>	93" (2,374 mm)
<b>Locking Positions</b>	1 (Adjustable)
<b>Lifting Time</b>	30 sec
<b>Standard Motor</b>	220 VAC / 60 Hz / 1Ph

\*Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult [www.autolift.org](http://www.autolift.org) for complete listings or contact BendPak via [contact@bendpak.com](mailto:contact@bendpak.com).