

R745



Tire Changer

SKU# 5140148

Swing Arm, 21" Capacity, 110V or 220V, 1-Phase, 50/60hz

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

No-Frills Tire Changer for Entry-Level Tire and Wheel Service.

The Ranger R745 [tire changer](#) is a rigid tower tire machine designed to handle the needs of heavy volume tire shops. A sturdy body, rigid 45mm hexagonal vertical shaft and hardened-steel horizontal outrigger support arm eliminate flex during all tire service procedures to reduce the chance of expensive wheels getting damaged.

A supersized turntable provides an internal clamping capacity of 21" and external clamping capacity of 18". With a long list of time-saving features, you'll safely mount low-profile performance tires and wheels with little effort.

Specifications

Motor	110 or 220 VAC, 50/60 Hz, 1 Ph
Drive System Type	Electric / Air
Air Requirement	110-175 PSI (8-12 BAR)
Wheel Clamping Method	4 Clamps - Internal / External
Table Clamping System	Dual Pneumatic Cylinders
Bead Breaking System	Pneumatic Blade
Tower Design	Fixed
Internal Rim Clamping Capacity	12" - 21" (304 mm - 533 mm)
External Rim Clamping Capacity	10" - 18" (254 mm - 457 mm)
Turntable Tire Width Capacity (Mounting)	5" - 12" (127 mm - 305 mm)
Bead Breaker Tire Width Capacity (Demounting)	3" - 11" (76 mm - 279 mm)
Maximum Tire Diameter	39" (991 mm)
Shipping Weight	486 lbs. (220 kg)



Standard Features

- Inflation Gauge With Integrated Air Dump Valve
- Brush
- Water Filter
- Tool Tray / Storage
- Breaker Bar
- Oiler / Lubricator
- Air Regulator
- Large Soap / Lubricator Bucket
- Inflation restraint