

SP-7X

Full-Rise Scissor Lifts

SKU# 5175144

7,000-lb. Capacity / Scissor Lift / Frame Engaging

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

The Full-Rise Scissor Lift with Collapsible Frames

This space-saving, frame-engaging [scissor lift](#) easily accommodates most passenger vehicles and light trucks and comes complete with pneumatic safety locks, rubber lifting blocks and an open-center for full under-car accessibility. Features a 21.5" x 63" lift platform, equalization torsion bar, hardened pivot pins, and ergonomic controls.

Features

- 7,000-lb. lifting capacity
- Pneumatic safety locks
- Equalization torsion bar
- Hardened pivot pins with "Zerk" fittings
- Open-center design
- Ergonomic controls
- Dual-cylinder hydraulic design provides extra power
- Low-profile



Specifications

Lifting Capacity	7,000 lbs. (3,175 kg)
Max. Lifting Height	68" (1,727 mm)
Overall Length	163.5" (4,153 mm)
Overall Width	74.5" (1,892 mm)
Lift Platform	21.5" x 63" (47 mm x 1,600 mm)
Lowered Height	5" (127 mm)
Width Between Pads	31.5" (801 mm)
Lifting Time	45 sec
Standard Motor	208-240 VAC / 50-60 Hz / 1 Ph
Shipping Weight	2,318 lbs. (1,054 kg)
Shipping Dimensions	106" x 76" x 46" (2,692 mm x 1,930 mm x 1,168 mm)

Note: An air supply (minimum 30 psi / 3 CFM) is required for the safety-lock mechanisms to disengage. It is solely the responsibility of the end-user to provide, install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.