

SP-7XF

Full-Rise Scissor Lifts

SKU# 5175135

7,000-lb. Capacity / Scissor Lift / Frame Engaging / Flush Mount

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

The Flush-Mount Version of Our Full-Rise Scissor Lift

The SP-7XF is the flush-mount version of our [full-rise scissor lift](#). If your garage has a recessed area of concrete designed to hold flush-mount lifts, you'll be pleased by how "invisible" this lift is in your garage. When it's collapsed, you're free to drive over it and work around it without tripping on wires or cables. We're proud that the collapsed SP-7XF is extremely low-profile, but if you want to take low to virtually zero, the flush-mount version of this model is the perfect car lift solution for your garage.

Features

- Pneumatic safety locks
- Equalization torsion bar
- Hardened pivot pins with "Zerk" fittings
- Open-center design
- Ergonomic controls
- Dual-cylinder hydraulic design provides extra power
- Low-profile
- Flush-mount



Specifications

Lifting Capacity	7,000 lbs. (3,175 kg)
Max. Lifting Height	68" (1,727 mm)
Overall Length	163.5" (4,153 mm)
Overall Width	74.5" (1,892 mm)
Lift Platform	21.5" x 63" (47 mm x 1,600 mm)
Lowered Height	5" (127 mm)
Width Between Pads	31.5" (801 mm)
Lifting Time	45 sec
Standard Motor	208-240 VAC / 50-60 Hz / 1 Ph
Shipping Weight	2,318 lbs. (1,054 kg)
Shipping Dimensions	106" x 76" x 46" (2,692 mm x 1,930 mm x 1,168 mm)

Note: An air supply (minimum 30 psi / 3 CFM) is required for the safety-lock mechanisms to disengage. It is solely the responsibility of the end-user to provide, install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.