

XPR-10AS



Two-Post Lifts

SKU# 5175397

10,000-lb. Capacity, Asymmetric Clearfloor, Adjustable Width, Screw Pads

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

XPR-10AS Two-Post Lift Protects Vehicles and Makes Lifting Easy

Every XPR-10AS [two-post lift](#) features Direct-Drive technology that's only available with BendPak. Every XPR-10AS features Direct-Drive technology that's only available with BendPak. The asymmetrical design of this lift has rotated columns, which makes it easier to enter and exit the vehicle and reduces the chance of door dings and dents. A 10K capacity BendPak car lift is a smart addition to any shop or garage.

Options

SKU#	Model	Description
5175398	XPR-10AS-LP	Low-Profile Arms
5175401	XPR-10AS-168	168" Overall Height
5175402	XPR-10AS-168-LP	168" OAH / Low-Profile

Features

- Expandable top beam for wide or narrow drive-thru
- Double-telescoping screw pads offer increased versatility
- Added overhead safety shutoff bar
- Tru-Metric arm design for more versatile arm positioning
- 30° rotated single-piece columns
- Single-point safety release
- Drop-end arms provide a lower pad height
- Dual hydraulic direct-drive cylinders
- Oversized 53" tall carriage for superior strength
- Electric / hydraulic power system
- Large, 17" x 19" A36 steel base plate
- Self-lubricating dura-glide UHMW polyethylene bearings
- Safety locks in each column spaced every 3"
- Automatic arm restraints
- Heavy-duty 1/2" aircraft-quality equalizer cables
- Oversized cable sheave diameter reduces cable fatigue
- 4-piece 63 mm stackable adapter set comes standard
- Triple-telescoping arm design
- Versatile drop-in contact pads with stackable adapters
- ETL Approved



Direct-Drive two-post car lift technology


BendPak XPR-10 two-post lifts feature low-pressure HVLP Direct-Drive cylinders: no more lifting chains or screws. Dual HVLP low-pressure cylinders minimize leakage, offer better reliability, smoother operation and fewer maintenance costs throughout the life of your lift. High volume and low pressure equates to less workload placed on the entire hydraulic system. Direct-Drive technology is preferred on commercial-grade two-post car lifts, as it has fewer moving parts than a chain-over-roller cylinder configuration. Pressurized hydraulic fluid flows from the power unit to the hollow cylinder rods, entering the cylinder body and filling its internal cavity. The pressure of the hydraulic fluid extends the piston rod downward, raising the cylinder body and lift carriages.

Two-stage telescoping screw pad assembly kit

Double-telescoping screw pads come standard with every asymmetrical 10K car lift. These polyurethane pads are ideal for intense shop environments and busy mechanics who can't afford money-sucking downtime. 63 mm stackable adapters are included for even more versatility.

Specifications

Model	XPR-10AS	XPR-10AXLS
Style	Asymmetric	Asymmetric / High Rise
SKU#	5175393	5175991
Lifting Capacity	10,000 lbs. (4,536 kg)	10,000 lbs. (4,536 kg)
A - Rise	69" (1,753 mm)	75" (1,905 mm)
B - Rise + Pad Only	73" (1,854 mm)	79.75" (2,025 mm)
C - Max. Lifting Height	79" (2,007 mm)	82.25" (2,088 mm)
D - Min. Height + Pad	4" (102 mm)	4.75" (120 mm)
E - Height Overall (*)	145" (3,683 mm)	157" (3,983 mm)
F - Width Overall	137" (3,480 mm) or 145" (3,683 mm)	137" (3,480 mm) or 145" (3,684 mm)
G - Outside Columns	133.25" (3,386 mm) or 141.25" (3,590 mm)	133.25" (3,386 mm) or 141.25" (3,590 mm)
H - Inside Columns	106.25" (2,700 mm) or 114.25" (2,903 mm)	106.25" (2,700 mm) or 114.25" (2,903 mm)
I - Drive-Thru Clearance	93.75" (2,382 mm) or 101.75" (2,585 mm)	93.75" (2,382 mm) or 101.75" (2,585 mm)
J - Floor to Top Switch (*)	141" (3,581 mm)	147" (3,734 mm)
K - Front Arm Reach (MIN)	23.5" (595 mm)	23.5" (595 mm)
K - Front Arm Reach (MAX)	43.75" (1,110 mm)	43.75" (1,110 mm)
L - Rear Arm Reach (MIN)	40.25" (1,024 mm)	40.25" (1,024 mm)
L - Rear Arm Reach (MAX)	58" (1,474 mm)	58" (1,474 mm)
Screw Pad Adjustment	2" (51 mm)	2" (51 mm)
Max. Load per Arm	2,500 lbs. (1,134 kg)	2,500 lbs. (1,134 kg)
Time to Full Rise	45 seconds	50 seconds
Noise	45 dB	45 dB
Motor	220 VAC / 60 Hz / 1 Ph	220 VAC / 60 Hz / 1 Ph



*Optional bolt-on top extension for columns raises the overall height and overhead safety bar an additional 24". Must be ordered from BendPak at time of order.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for a complete list or contact BendPak via contact@bendpak.com.