

# XPR-12CL-LTA



## Two-Post Lifts

SKU# 5175258

12,000-lb. Capacity / Two-Post Lift / Clearfloor / 72" Long-Reach Telescoping Arms

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

## XPR-12CL-LTA Offers Long-Reach, Heavy-Duty Lifting

Finding the lift points on bigger trucks and vehicles with a two-post lift can often be a challenging procedure. When lift arms are too short, they need to be moved closer together to reach the vehicle lift points and this makes it hard to find the vehicle's center of balance on especially long wheelbases. But the new BendPak XPR-12CL-LTA solves this problem and allows you to reach even the longest, most difficult wheelbases in the industry. The XPR-12CL-LTA features three-stage telescoping lift arms with a 72" maximum range, extending even further than the 58" on our standard XPR-12CL two-post lift series. This broader option allows you to find the center of balance on the biggest trucks around, giving you the versatility and power to safely lift any vehicle up to its 12,000-lb. capacity.



### The XPR-12CL-LTA is ALI Certified

The Automotive Lift Institute (ALI) is the golden standard of automotive lift safety. With their ANSI accreditation, ALI is the only nationally recognized institute for lift certification. An ALI Certification assures you that the automotive lift in your garage meets with the quality and safety standards developed by ALI over the last 74 years of its operation. A lift that is ALI Certified had to meet with rigorous safety standards to determine the safety of its structural integrity, design, components, manual instruction and production facility.

### Lift Carriages Strengthened to Handle Long Reach

Along with its extended reach, the XPR-12CL-LTA features extra carriage strength to counter the extra weight of the extra-long arm.

### Optional column extension

BendPak can increase your overhead clearance to 192" overall height to maximize the number vehicle types you can service in this weight class.

## Options

SKU#	Model	Description
5175405	XPR-12CL	Standard
5175407	XPR-12CL-192	192" Overall Height
5175259	XPR-12CL-192-LTA	192" OAH / Long-Reach

## Features

- CE Approved and Certified.
- Padded overhead safety shutoff bar
- Extended height top-beam provides greater clearance
- Single-point safety release
- Dual direct-drive hydraulic cylinders
- Dual-synchro equalization system for equal lifting
- Oversized 53" tall carriage for superior strength
- Electric / hydraulic power system
- Oversized A36 steel base plates
- Self-lubricating dura-glide UHMW polyethylene bearings
- Safety locks in each column spaced every 3"
- Automatic arm restraints
- Heavy-duty 1/2" aircraft-quality equalizer cables
- Oversized cable sheave diameter reduces cable fatigue
- Durable, rubber lift pads with stackable adapters
- 16-piece specialty adapter set includes four 6" stackable adapters, four 3" stackable adapters, four polyurethane contact pads and four frame cradle pads
- Convenient storage is included for truck and van adapters
- Triple-telescoping arms provide increased range

# Specifications



Model	XPR-12CL-LTA	XPR-15CL	XPR-18CL
SKU#	5175258	5175408	5175409
Lifting Capacity	12,000 lbs. (5,443 kg)	15,000 lbs. (6,804 kg)	18,000 lbs. (8,165 kg)
<b>A - Rise</b>	69" (1,753 mm)	69" (1,753 mm)	69" (1,753 mm)
<b>B - Rise + Pad Only</b>	74" (1,880 mm)	74" (1,880 mm)	74" (1,880 mm)
<b>C - Max. Lifting Height</b>	80" (2,032 mm)	80" (2,032 mm)	80" (2,032 mm)
<b>D - Min. Height + Pad</b>	5" (127 mm)	5" (127 mm)	5" (127 mm)
<b>E - Height Overall (*)</b>	170" (4,318 mm)	170" (4,318 mm)	170" (4,318 mm)
<b>F - Width Overall</b>	155" (3,937 mm)	155" (3,937 mm)	155" (3,937 mm)
<b>G - Outside Columns</b>	144" (3,658 mm)	144" (3,658 mm)	144" (3,658 mm)
<b>H - Inside Columns</b>	120" (3,048 mm)	120" (3,048 mm)	120" (3,048 mm)
<b>I - Drive-Thru Clearance</b>	106" (2,692 mm)	106" (2,692 mm)	106" (2,692 mm)
<b>J - Floor to Top Switch (*)</b>	165" (4,191 mm)	165" (4,191 mm)	165" (4,191 mm)
<b>K - Front Arm Reach (MIN)</b>	37" (940 mm)	39" (991 mm)	39" (991 mm)
<b>K - Front Arm Reach (MAX)</b>	72" (1,829 mm)	60" (1,524 mm)	60" (1,524 mm)
<b>L - Rear Arm Reach (MIN)</b>	37" (940 mm)	39" (991 mm)	39" (991 mm)
<b>L - Rear Arm Reach (MAX)</b>	72" (1,829 mm)	60" (1,524 mm)	60" (1,524 mm)
<b>Screw Pad Adjustment</b>	Not Compatible	Not Compatible	Not Compatible
<b>Max. Load per Arm</b>	3,000 lbs. (1,361 kg)	3,750 lbs. (1,701 kg)	4,500 lbs. (2,041 kg)
<b>Time to Full Rise</b>	90 seconds	90 seconds	90 seconds
<b>Noise</b>	45 dB	45 dB	45 dB
<b>Motor</b>	220 VAC / 60 Hz / 1 Ph	220 VAC / 60 Hz / 1 Ph	220 VAC / 60 Hz / 1 Ph

\*Optional bolt-on top extension for columns raises the overall height and overhead safety bar an additional 24". Must be ordered from BendPak at time of order.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/JUL 201. Consult [www.autolift.org](http://www.autolift.org) for a complete list or contact BendPak via [contact@bendpak.com](mailto:contact@bendpak.com).

