# RB24T



#### **Wheel Balancers**

SKU# 5140149

Truck Wheel Balancer with Deluxe Adapter Kit and Quick-Chuck, 208-240V, 1-Phase, 50/60hz

## The Super-Duty Truck Balancer

The Ranger RB24T truck wheel balancer is a heavyweight wheel balancer suited especially for high-volume commercial tire dealers and truck fleets. Most bargain brand balancers on the market are simply standard balancers with larger mounting cones. Those less advanced truck balancers take their sweet time getting heavy wheels spinning up to speed and just as long to get those heavy wheels to stop.

# **Specifications**

Power Supply	208 – 240V, 50 / 60 Hz, 1 Ph
Drive Motor	1.5 HP, 380V, 50 / 60 Hz, 3 Ph
Working Temperature	-5°C / 27°F - 50°C / 82°F
Drive System	Ribbed Nylon Fiber Drive Belt
Cycle Time	7 - 10 seconds (avg.)
Balancing Modes	1 Dynamic / 1 Static / 3 Alloy
Wheel Spin Braking	Electronic Pulse / Pneumatic Brake
Wheel Hold Device	Pneumatic Brake
Shaft Size	40 mm
Centering Cones Included	5 Standard / 1 Dual Tapered Cone
Max. Tire Diameter	50" (1,270 mm)
Max. Tire Diameter  Max. Tire Weight	50" (1,270 mm) 400 lbs. (181 kg)
Max. Tire Weight	400 lbs. (181 kg)
Max. Tire Weight  Max. Wheel Diameter	400 lbs. (181 kg) 30" (762 mm)
Max. Tire Weight  Max. Wheel Diameter  Wheel Width Capacity	400 lbs. (181 kg) 30" (762 mm) 2" - 20" (51 mm - 508 mm)
Max. Tire Weight  Max. Wheel Diameter  Wheel Width Capacity  Balancing Increments	400 lbs. (181 kg) 30" (762 mm) 2" - 20" (51 mm - 508 mm) 0.25 or 0.01 oz
Max. Tire Weight  Max. Wheel Diameter  Wheel Width Capacity  Balancing Increments  Balancing Speed	400 lbs. (181 kg) 30" (762 mm) 2" - 20" (51 mm - 508 mm) 0.25 or 0.01 oz 220 RPM
Max. Tire Weight  Max. Wheel Diameter  Wheel Width Capacity  Balancing Increments  Balancing Speed  Accuracy / Standard	400 lbs. (181 kg)  30" (762 mm)  2" - 20" (51 mm - 508 mm)  0.25 or 0.01 oz  220 RPM  +/- 1 g (.03 oz.) - Cars & Light Trucks

### **Questions? Contact BendPak's Sales Team**

sales@bendpak.com | 1-800-253-2363 Monday - Friday, 7AM to 4:30PM PST



The RB24T truck wheel balancer handles tires up to 50" in diameter, 20" wide and rim sizes up to 30" in diameter. Although best suited for bus, truck and OTR wheels, it's also capable and fully equipped to accommodate light truck wheels as well. An integrated wheel lift easily lifts the heaviest wheel assemblies for effortless mounting on the balancer.

### **Standard Features**

- Integrated power phase converter
- Top positioning weight locator
- Inside & outside measuring
- Millimeter / inches selection
- Ounce / gram selection
- Self-calibration function
- Auto start when hood is lowered
- Ouick chuck kit
- Adjustable flange plate and stud kit
- Multi-piece mounting cone kit
- Wheel calipers