

# RCD-1500



## Carts and Dollies

SKU# 5150595

1500-Lb. Capacity Go-Cart™ Car Dollies, 12" Tire Width, 28" Tire Diameter, Sold as Pair

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

## The GoCart™ is the Ultimate Car Dolly and Wheel Lift

Sold in sets of two, these [car dollies](#) are the wheels for your wheels. Ranger Products GoCart car dollies make moving your vehicle painless for you and your employees. Take advantage of precious floor space by effortlessly moving your vehicle against a wall, into a tight space or around a corner with the help of GoCart dollies. They offer precise positioning power without having to turn on your car or truck. Ideal for moving dead cars and trucks up to 6,000 lbs. With a complete set of four car dollies, GoCart allows one person to effortlessly move cars, trucks, boats, trailers, lawn mowers and tractors, jet skis, motorcycles, airplanes or other wheeled and recreational vehicles with ease. Note: operators may require assistance stopping vehicles once they start rolling on GoCart car dollies by Ranger Products.

Operation procedures for the GoCart mobile car dolly could not be simpler. Simply extend the telescoping GoCart to its maximum width. Next, roll the GoCart over to the vehicle so the aluminum rollers "hug" the tire. Twist close the valve and repeatedly step on the foot pump. The GoCart rollers will quickly and smoothly engage the tire and prop up that quarter of the vehicle. Once you have reached the desired height, secure the pump mechanism into place and insert the pin into one of the GoCart's elevation locks. Do this for each desired wheel and you'll experience GoCart's easy-rolling car dolly perfection in no time.

## Features

- Heavy-duty steel construction
- Available in sets of two or four
- Durable powder-coat finish
- Flat free polymer wheels for easy rolling
- Non-skid polymer rollers resist load slippage
- Expandable frame accommodates variable tire sizes
- Move heavy loads with confidence and ease



## Specifications

<b>Load Rating (ea.)</b>	1,500 lbs. (680 kg)
<b>Load Rating Total</b>	6,000 lbs. (2,722 kg)
<b>Lifting Mechanism</b>	Hydraulic Foot Pump
<b>Tire Width Capacity</b>	12" (305 mm)
<b>Tire Diameter Capacity</b>	15" - 28" (381 mm - 711 mm)
<b>Wheel Size Capacity</b>	8" - 24" (203 mm - 610 mm)
<b>Overall Height</b>	6" (152 mm)
<b>Casters Diameter</b>	4" (102 mm)
<b>Stowed Dimensions</b>	21" x 24" (533 mm x 610 mm)
<b>Caster to Handle</b>	18" (457 mm)
<b>Unit Weight</b>	42 lbs. (19 kg)
<b>Mobile Storage Rack</b>	Optional