

# SP-7XLF

## Full-Rise Scissor Lifts

SKU# 5175993

7,000-lb. Capacity / Scissor Lift / Frame Engaging / Flush Mount

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

## The Flush-Mount Version of Our Full-Rise Scissor Lift

The SP-7XLF is the flush-mount version of our [full-rise scissor lift](#). If your garage has a recessed area of concrete designed to hold flush-mount lifts, you'll be pleased by how "invisible" this lift is in your garage. When it's collapsed, you're free to drive over it and work around it without tripping on wires or cables. We're proud that the collapsed SP-7XLF is extremely low-profile, but if you want to take low to virtually zero, the flush-mount version of this model is the perfect car lift solution for your garage.

## Features

- Pneumatic safety locks
- Hardened pivot pins with "Zerk" fittings
- Open-center design
- Ergonomic controls
- Dual-cylinder hydraulic design provides extra power
- Low-profile
- Flush-mount



## Specifications

<b>Lifting Capacity</b>	7,000 lbs. (3,175 kg)
<b>Max. Lifting Height</b>	70.5" (1,791 mm)
<b>Overall Length</b>	105.5" (2,692 mm)
<b>Single Platform Length</b>	62.5" (1,590 mm)
<b>Single Platform Width</b>	22" (554 mm)
<b>Overall Width - Min</b>	81.5" (2,072 mm)
<b>Overall Width - Max</b>	87.5" (2,222 mm)
<b>Lowered Height</b>	Flush with concrete
<b>Lifting Time</b>	45 sec
<b>Standard Motor</b>	208-240 VAC / 50-60 Hz / 1 Ph

Note: An air supply (minimum 30 psi / 3 CFM) is required for the safety-lock mechanisms to disengage. It is solely the responsibility of the end-user to provide, install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult [www.autolift.org](http://www.autolift.org) for complete listings or contact BendPak via [contact@bendpak.com](mailto:contact@bendpak.com).